25'(5$%/('(9,&(	3$&.$*,1* 7<3(	67$1'$5' 3$&. 47<	3$&.$*(0$5.,1*	3,16	3$&.$*('(6&5,37,21	06/

SCT CONFIDENTIAL

SCT CONFIDENTIAL

3$5$0(7(5	'(),1,7,21	0,1	0$;	81,7

3$5$0(7(5	'(),1,7,21	0,1	0$;	81,7

3$5$0(7(5	7+(50$/ 0(75,&	)&4)1 /	81,7

SCT CONFIDENTIAL

SCT CONFIDE

6<0%2/	3$5$0(7(5	7(67 &21',7,21	0,1 7<3 0$;	81,7
3RZHU *RRG				
		POWER GOOD (% of FB voltage)		
		POWER BAD (% of FB voltage)		
		POWER BAD (% of FB voltage)		
		POWER GOOD (% of FB voltage)		
		VPull-Up = 5V		
		IPull-Up = 1 mA		
3URWHFWLRQ				

SCT CONFIDENTIAL

SCT CON



SCT CONFIDENTIAL

2YHUYLHZ

SCT CONFIDENTIAL

SCT CONFIDENTIAL

SCT CONFI

3RZHU*URRG

7KHUPDO 6KXWGRZQ

SCT CONFIDENTIAL

2XWSXW 9ROWDJH

9287	5	5

$_5 = (\frac{\quad}{\quad} - 1)$ $_6$

6ZLWFKLQJ)UHTXHQF\

)VZ	5 56:

$_3(K\Omega) = (\frac{1}{(\quad)} - 3.3 \times 10^{-5}) \times 2.04 \times 10^{4}$

8QGHRJO9WDJHRIF2XW

$$= (\frac{1}{2} + 1) \times$$

$$= (\frac{1}{2} + 1) \times$$

SCT CONFIDENTIAL

,QGXFWRU 6HOHFWLRQ

SCT CONFIDENTIAL

, QSXW & DSBFHOWRWLRQ

$$I_{CINRMS} = I_{OUT} \sqrt{\frac{V_{OUT}}{V_{IN}} (1 - \frac{V_{OUT}}{V_{IN}})}$$

$$I_{CINRMS} = 0.5 \ I_{OUT}$$

$$\Delta V_{IN} = \frac{I_{OUT}}{f_{SW} \ C_{IN}} \frac{V_{OUT}}{V_{IN}} (1 - \frac{V_{OUT}}{V_{IN}})$$

SCT CONFIDENTIAL

7DEOH7\SLFDO ([WHUQDO &RPSRQHQW 9DOXHV

SCT CONFIDENTIAL

$SSOLFDWLRQ :DYHIRUPV













/ D \ R X W L G H O L Q H

1.

2.

3.

4.

5.

6.



SCT CONFIDENTIAL



TOP VIEW **BOTTOM VIEW**



SIDE VIEW



SECTION A-A



RECOMMENDED LAND PATTERN

NOTE:

1) THE LEAD SIDE IS WETTABLE.
2) ALL DIMENSIONS ARE IN MILLIMETERS.
3) EXPOSED PADDLE SIZE DOES NOT INCLUDE MOLD FLASH.
4) LEAD COPLANARITY SHALL BE 0.08 MILLIMETERS MAX.
5) DRAWING CONFIRMS TO JEDEC MO-220.
6) DRAWING IS NOT TO SCALE.





PRODUCT SPECIFICATIONS

W2	TYPE WIDTH	ØA	ØN	W1
19.4	12MM	330±2.0	100±1.0	12.4
23.4	16mm	330±2.0	100±1.0	16.4
31.4	24MM	330±2.0	100±1.0	24.4
39.4	32MM	330±2.0	100±1.0	32.4
105±1.0	44.4	5.14	44MM	330±2.0

SYMBOL	A0	B0	K0	P0	P1	P2
.10	2.00±0.05	SPEC	4.30±0.10	4.30±0.10	1.10±0.10	4.00±0.10	8.00±0
		SYMBOL	T	E	F	D0	D1
.10	12.00±0.30	SPEC	0.30±0.05	1.75±0.10	5.50±0.05	1.55±0.05	1.55±0



NOTE:
1. 材料：黑色防静电复合PS；
2. 10个链孔的累积公差不能超过±2mm；
3. 250mm距下的扭转不得超过2mm；
4. 所有尺寸符合EIA-481-E的要求。



)HHGLQJ 'LUH