

UE V4666S

REVISION HISTORY

DEVICE ORDER INFORMATION

QTFGTCDNG FGXIEG'	RCEMCI RPI V RG'	UVCPTCTF RCEM'SV	RCEMCI G OCTMRPI	RIPU	RCEMCI G' FGUETIRVIQP	OUN

ABSOLUTE MAXIMUM RATINGS

PIN CONFIGURATION

FGUETIRVIQP

OR OCZ

UE V4666S

RECOMMENDED OPERATING CONDITIONS

RCTCOGVGT	F GHPW/QP	OK	OCZ	WPW

ESD RATINGS

RCTCOGVGT	F GHPW/QP	OK	OCZ	WPW

THERMAL INFORMATION

RCTCOGVGT	VJGTOCN'OGVTIE	HE S HP50 z6/36N	WPW

ELECTRICAL CHARACTERISTICS

& &

U ODQN	RCTCOGVGT	VGUV'EQPFV/QP	OKP	V R	OCZ	WPKV
--------	-----------	---------------	-----	-----	-----	------

Rqy gt'Uwr r n

		&				
		&	&			
		&				
		&				
		&	&	&		
		&	&	&	&	

XEE'NFQ

Rqy gt'OQUHGU

		&				

Tghgtgpeg'cpf'Eqpvtqr/Nqqr

--	--	--	--	--	--	--

E wttgpn'Nlo k'cpf'Qxgt'E wttgpn'Rtqgcvqp

		&				
		&				
		&				
		&				
		&				

Gpcdrq'cpf'Uqh/Uctwr







Uy ke j lpi 'Htgs wpe "cpf"Gzvgtpcn'Ergen/U pe j tqpk cvqp

		&				
		&				


UE V4666S

U ODQN	RCTCOGVGT	VGJVEQPFK/QP	OR	V R	OCZ	WPK
Rqy gt'l qqf						
		POWER GOOD (% of FB voltage)				
		POWER BAD (% of FB voltage)				
		POWER BAD (% of FB voltage)				
		POWER GOOD (% of FB voltage)				
		VPull-Up = 5V				
		IPull-Up = 1 mA				
Rtqgvevqp						

TYPICAL CHARACTERISTICS



FUNCTIONAL BLOCK DIAGRAM




OPERATION

Qxgtxlgy

UE V4666S

Gpcdrq"cpf "Wpf gt"Xqnci g"Nqenqww"Vj tguj qrf "




"

Htgs wgpe "Ur tgc f "Ur gev two

XEE "NF Q."XEE "WKNQ."cpf "DICU" for w

Dqqwvtr "Xqnci g" Tgi wcvqt" cpf "Nqy "F tqr /qw" Qr gtcvqp



&

Qxgt'E wttgpvNlo W'cpf "J leewr "Oqf g


Qxgt'xqnci g'Rtqvgevkqp

Rqy gt'l qqf "

Vj gto cñUj wf qy p

APPLICATION INFORMATION

V r lecrnC r rlecVqp



Hk wtg"340UE V4666S"F guk p"Gzco r rg." X"Qwr wly kj"Cfl wuvcdrg"WKNQ

F guk p'Rctco gvgtu

F guk p'Rctco gvgtu	Gzco r rg"Xcnvg
	&

Qwr w'Xqnci g

X _{QW}	T	T

Uy ke j lpi 'Htgs wgpe

Huy	T ₅ " T _{HUY}

Wpf gt'Xqnci g'Nqem/Qwr

&

&

Íþf wevqt'Ugrgevkqp

Kör w'Ecr cekqt'Ugrgevqp


&

Dqqwvtr'Ecr cekqt'Ugrgevqp


Qwr w'Ecr cekqt'Ugrgevqp

Y R W D T P V Q T M C W O S J R % R X W Ü Ê h K H W V R X S H ð T M O T M


Cr r necVqp"Y cxghqto u
& &



&




&





"

&






&




UE V4666S


Cr r decVqp"Y cxghqto u




&



&





&




Nc qw'l wf grpg

TAPE AND REEL INFORMATION



A-A

Hggf lpi 'F kgevkap



外观	尺寸 (MM)
E	1.75±0.10
F	5.50±0.05
P2	2.00±0.05
D	1.55±0.05

外观	尺寸 (MM)
W	12.00 ^{+0.30} _{-0.10}
P	8.00±0.10
A0	3.75±0.10
B0	4.25±0.10

D1	1.50MIN	K0	1.10±0.10
P0	4.00±0.10	θ	5°T.V
10P0	40.0±0.20		